RELEASE

Carpet Tile Series



EXCEL®

What are carpet tiles

Carpet tiles are specially designed squares of carpeting that are made to lockdown in a similar way to standard carpet flooring. Some of the tiles adhere to the floors using glues, while others are nailed or stapled down. This carpet flooring option is designed to go down easily, and it's often used with different colors blended together in checker or mosaic patterns to create more unique looks. While not everyone likes the look of carpet tiles, it's a strong type of carpet flooring that's coming back in style today.

The advantage of carpet tiles

If you're looking for a quick and easy to install type of carpet flooring, tiles are the perfect way to go. When it comes to carpet installation, tiles are one of the best products on the market. They go down very quickly and easily and are designed for simplicity. Since carpet flooring tiles are designed to be small in size, they are easy to carry and to position wherever they are needed. This is much simpler than carrying around large rolls of roll-out carpet varieties. Carpet tiles go down faster during carpet installation than other carpet flooring types as well, and it doesn't take as much skill to ensure that the floor looks smooth and even.

- Cost and time savings
- Simple and fast installation:
- Extremely durable:
- Easy to maintain:
- Huge options:

RELEASE
Carpet Tile Series

Overview
FRESH CARPET
Looks



RL-02



RL-04



RL-06



RL-07

NOTE

- Photos are showing only the design patterns.
- The color of the sample pasted is only showing part of the actual carpet.
- Specifications are subject to change when they improve product.
- Slight colour variations may occur from dye lot to dye lot.



RL-02



RL-04


RL-06



RL-07

SPECIFICATION

Product Name	RELEASE
Construction	Multi-level loop
Yarn Type	100% Polypropylene (PP)
Dye Method	100% Solution Dyed
Machine Guage	5/64"
Stitches	10 per inch
Pile Height	3.5mm(±0.5mm)
Total thickness	5.5mm (±0.5mm)
Pile Weight	610 g/m^2
Total weight	3300±100 g/m^2
Primary Backing	Non Woven Synthetic
Second Backing	Bitumen
Tile Size	50cm×50cm
Area of use	Heavy commercial
Packing	20 tiles/carton (5sqm/Carton)
Flammability	Passes ASTM D2859-16
Smoke Density	Passes ASTM E 662 < 450
Dimensional Stability	ASTM D7570/AACHEN < 0.2%
Tuft Bind	ASTMD1335 >7.8 lbs
Static Propensity	Passes AATCC-134 < 3.5KV
Stain Resistance	AATCC 175-2003 Rating 10
Colorfastness to Crocking	Rating 5, AATCC Test Method 165
Colorfastness to Light	Rating 5, AATCC Test Method 16.3
Indoor Air Quality	CRI Green Label Plus GLP1727


WARRANTIES

5 YEARS GENERAL WARRANTY

EXCEL IMPORT PVT LTD hereinafter called EXCEL CLASSIC FLOORS warrants to its customer that all polypropylene carpet tiles IMPORTED by EXCEL IMPORT PVT LTD will be first quality and will be free from manufacturing defects within general accepted standard of industry. If there is a manufacturing defect, a EXCEL representative must be notified immediately by the end user in writing. Written notification must include description of said defects, together with proof of purchase to the party (seller) from whom the product was purchased. Allow 2-4 weeks for processing.

After notification to EXCEL, EXCEL representative will, if necessary, inspect and verify the defect, if such defect is verified, EXCEL will, at its option, arrange for repair or replacement of the defective carpet.

INSTALLATION METHODS



DISCLAIMERS

- According to international Carpet manufactured norms color may differ from dye lot to dye lot within tolerance.
- Please take note of the day lot number on the cartons before installing the tiles.
- Recommended laying of Carpet tiles : Checkered board pattern.